

## CENTRAL INTELLIGENCE AGENCY

## INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

SECRET/CONTROL - U.S. OFFICIALS ONLY  
SECURITY INFORMATION

25X1

COUNTRY	East Germany	REPORT	
SUBJECT	Pithead Installations of Wismut A.G.	DATE DISTR.	27 February 195
		NO. OF PAGES	3
DATE OF INFO.		REQUIREMENT NO.	RD
PLACE ACQUIRED		REFERENCES	25X1

This is UNEVALUATED Information

THE SOURCE EVALUATIONS IN THIS REPORT ARE DEFINITIVE.  
THE APPRAISAL OF CONTENT IS TENTATIVE.  
(FOR KEY SEE REVERSE)

25X1

Equipment installed at pitheads of Objects 1, 2, 8, 14, 29, 30, and 90 of the Wismut A.G., Headquarters of the Third Directorate, Siegmars-Schoenau, is as follows:

1. Object 1, Pit Ellnere

Mechanical equipment for a Grade III bunker, capacity 150 m<sup>3</sup>

5 forward car-tippers	(Stirnkipper)
1 sliding platform	(Schiebebühne)
5 slide-releases	(Schiebeverschlüsse)
1 winch, OKI (diam:400mm)	(Foerderhaspel)
35 meters of cable	(Foerdersseil)
7 cable pulleys	(Seilrollen)
4 switches (railway)	(Weichen)
65 meters of track	(Gleis)

2. Object 2, Pit 310

a. Pit-head light railway complex (Wagenumlauf)

4 off-loading platforms for cage	(Foerderkorbanschlusseebühnen)
6 electromagnetic switch-operating relays	(elektrische magnetische Weichenantriebe)
6 electromagnetic stoppers	(elektrische magnetische Stopper)
2 automatic switches	(Automatische Weichen)
1 chain elevator K.20	(Kettenaufzug)
1 chain elevator K.22	(Kettenaufzug)
4 car braking appliances	(Wagenabstossvorrichtungen)
4 hand stoppers	(Handstopper)
5 track brakes	(Gleisbremsen)
5 right-hand switches	(Rechtsweichen)
9 double crossover switches	(Uebergleis Weichen)
2 single crossover switches	(Kreuzweichen)
860 meters of mine rails	(Grubenschienen)

STATE	X	ARMY	X	NAVY	X	AIR	X	FBI		AEC	X			OSI/NEO	BY	X
-------	---	------	---	------	---	-----	---	-----	--	-----	---	--	--	---------	----	---

(Notes: Washington Distribution Indicated By "X"; Field Distribution By "#".)

SECRET/CONTROL - U.S. OFFICIALS ONLY

25X1

- 2 -

b. Grading installation (Sortieranlage)

- 5 conveyor belts (length 38-40 m)
- 1 conveyor belt (length 7 m)
- 5 pairs of conveyor belts (length 2.5 - 3.0 m)
- 4 bunker locks
- 35 chutes, various

(Transportbaender)  
(Transportband)  
(5 Satz (a ? Stueck)  
(Transportbaender)  
(Bunkerverschluesse)  
(diverse Schurren)

c. Inclined hoist installation (Terrakonik)

- 2 haulage cables (diameter 18.5; length 500 m)
- 2 terraconic switches (gauge: 1200 mm)

(Foerderseile)  
(Terrakonikweichen)

3. Object 8, Pit 332 Adit II (Stollen 2)Additional mechanical equipment

- 1 rotary car tipper
- 2 forward car tipplers
- 1 sliding platform
- 3 segment bunker locks
- 1 foot-stopper
- 8 switches (railway)
- about 100 meters of track
- 2 concrete ore-bunkers for Grade I & II ore;  
capacity 18 m<sup>3</sup>
- 1 dead-rock bunker capacity 7 m<sup>3</sup>

(Kreiselwipper)  
(Stirnwipper)  
(Schiebebuehne)  
(segment. Bunkerverschluesse)  
(Fusstopper)  
(Weichen)  
(Gleis)  
(Beton Erzbunker fuer 1.  
und 2te Sorte)  
(Totgesteinbunker)

4. Object 14, Pit 347

- 1 steel bunker (capacity 60 m<sup>3</sup>)

(Stahlbunker)

5. Object 29

- 2 gasoline tanks (capacity 35 & 40 tons)

(Benzintank)

6. Object 30, Pit 350.

Technologisches Komplex; provisorische Estakade fuer Herrenbefoerderung  
von Totgestein fuer Terrakonikbunker 1

- 2 off-loading platforms for cage
- 2 sliding platforms
- 1 haulage winch (diam: 2200 mm)
- 1 rotary car tipper
- 2 terraconic skips (capacity: 1.7 m<sup>3</sup>)
- 2 tipping frames with guide roller and frame

(Foerderkorbanschlusseuehne)  
(Schiebebuehnen)  
(Foerderhaspel)  
(Kreiselwipper)  
(Terrakonik Skips)  
(Abwurfrahmen mit fuehrender  
Rolle mit Rahmen)  
(Schienen)  
(Terrakonikweiche)  
(Uebergleis Weiche)

100 meters of rails

- 1 terraconic switch
- 1 double crossover point

7. Object 90, Pit 352

- 1 shaking sieve with hook (Aufhaenger) (1250/2500)
- 2 off-loading platforms for cage)
- 2 foot-stoppers
- 2 pneumatic bunker locks

(Schwingsieb)  
(Foerderkorbanschlusshuehner)  
(Fusstopper)  
(pneumatische Bunkerver-  
schluesse)

- 2 grids (width of openings 200 mm & 150 mm)
- 1 grading device
- 1 grading belt (width 500 mm; length 4-5m)
- 2 conveyor belts (width 500 mm; length 15m)
- 1 conveyor belt (width 500 mm; length 20 m)

(Roeste)  
(Sortiereinrichtung)  
(Pruefband)  
(Transportbaender)  
(Transportband)

SECRET/CONTROL - U.S. OFFICIALS ONLY

SECRET/CONTROL - U.S. OFFICIALS ONLY

25X1

- 3 -

120 meters of track  
3 points  
5 chutes, various  
1 chute lengthener  
1 inclined-hoist installation  
1 haulage winch OK.1 (diam: 400mm)

(Gleis)  
(Weichen)  
(diverse Schurren)  
(Schurrenverlaengerung)  
(TerraKonikanlage)  
(Foerderhaspel)

25X1

1. Comment. Technological complex: temporary palings for the loading of dead rock for inclined hoist installations. "Estakade" is a germanized version of the French term estacade.

SECRET/CONTROL - U.S. OFFICIALS ONLY